


Included in the package:

- Talis with CR2430 battery installed.
- CD or DVD (Manual, PC Interface program).


Included or optional:

- Mac app.

WATCH MODE (Main Time)



NORM MODE (Surface)



SET GAS

Gas 1 - FO2, PO2 Alarm
Gas 1 - FO2, PO2 Alarm
FO2 50% Default

SET ALARMS


Audible
Depth
Elapsed Dive Time
NiBG
Dive Time Remaining

SET UTILITIES


Wet Activation
Units
Deep Stop
Safety Stop
Conservative Factor
Backlight Duration
Sampling Rate

A+S 2s
Serial Number


GAUG MODE (Surface)



NORM (Surface)



NORM (Dive)



Deep Stop




at 1/2 Max Depth for
2 min after Depths
> 80 FT (24 M)

Safety Stop



at 15 FT (5 M) for
3 min after Depths
> 30 FT (9 M)

FREE MODE (Surface)



from
Main

A+S
2s

SET ALARMS


A < 2s

A 2s

Elapsed Dive Time
Depth 1
Depth 2
Depth 3

to Set:
S hold (scroll up)
S < 2s (step up)
M < 2s (step down)
A < 2s (save setting)


GAUG (Surface)



GAUG (Dive)



FREE (Surface)



FREE (Dive)

